

FS125E



Little, powerful electric - floor saw

- Adjustable anti vibration handles for operators comfort
- Cutting depth adjustment by handwheel
- Cutting depth indicator
- Front cutting guide
- Parking break
- Big rear wheels for good chassis clearance
- External water connection

Compact floor saw with electric motor



Parking break

CIE



Adjustable anti vibration handles for operators comfort

FS125E



Cutting depth locking device



Cutting depth adjustment by handwheel



Powerful electric enginge



Cutting depth indicator



On-off-switch with motorstop

| Specification | GÖLZ FS125E | |
|--------------------------|------------------------------|-------|
| Max Cutting depth | 120 mm | |
| Blade diameter | (max.) 350 mm | |
| Shaft size | 25,4 mm | |
| Engine | 3 kW (4 HP); 400 V; 50-60 Hz | |
| Shaft speed | 2.880 min ⁻¹ | |
| Water connection | external | |
| Feed motion | Push | |
| Cutting depth adjustment | Handwheel | |
| Power transmission | 3 x V-belt | |
| Hand Arm Vibrations | 4,5 m/s ² | |
| Dimensions (LxWxH) | 650 x 450 x 1.000 mm | |
| Weight | 77 kg | |
| | | - |
| | Order Number | Price |



All prices in EURO ex works Hellenthal. Product changes, technical changes and mistakes reserved. Our terms of sale, delivery and payment apply exclusively. © Copyright 2016 by Gölz GmbH Hellenthal.

0282 125 600